


**Insulated cable end-sleeves, acc. to DIN, Easy Entry**

- ▶ For fine and superfine stranded conductors
- ▶ Easy-Entry insulation for easy cable insertion
- ▶ Crimped cable end-sleeves for easy mounting to cable clamps



**Characteristics**

- Total cross-section: 0.5 - 150 mm<sup>2</sup>
- Colour-coding and tube dimension to DIN 46228, part 4 (0.5 - 50 mm<sup>2</sup>)
- Halide free
- Heat resistant to 105° C

**Material**

- Copper acc. to EN 13600
- Synthetic material: polypropylene

**Surface**

- Tin-plated to protect against corrosion

**Order info**

- Now also available in handy plastic boxes for smaller requirements, part number appendix "SB"

Nominal cross section mm <sup>2</sup>	Part No.	Colour	Dimension mm					Weight/ 1000 pcs.~ kg	Packing unit/ pcs
			d1	d3	l1	l2	s1		
0.5	4696	□	1.0	3.1	12	6	0.15	0.070	1000
	4698	□	1.0	3.1	14	8	0.15	0.070	1000
	GR4698	□	1.0	3.1	14	8	0.15	0.070	500 ***
	46910	□	1.0	3.1	16	10	0.15	0.085	1000
0.75	4706	■	1.2	3.3	12	6	0.15	0.080	1000
	4708	■	1.2	3.3	14	8	0.15	0.080	1000**
	GR4708	■	1.2	3.3	14	8	0.15	0.080	500 ***
	47010	■	1.2	3.3	16	10	0.15	0.100	1000
1	47012	■	1.2	3.3	18	12	0.15	0.105	1000
	4716	■	1.4	3.5	12	6	0.15	0.090	1000
	4718	■	1.4	3.5	14	8	0.15	0.100	1000**
	GR4718	■	1.4	3.5	14	8	0.15	0.100	500 ***
1.5	47110	■	1.4	3.5	16	10	0.15	0.120	1000
	47112	■	1.4	3.5	18	12	0.15	0.125	1000
	4726	■	1.7	4.0	12	6	0.15	0.105	1000
	4728	■	1.7	4.0	14	8	0.15	0.110	1000**
2.5	GR4728	■	1.7	4.0	14	8	0.15	0.110	500 ***
	47210	■	1.7	4.0	16	10	0.15	0.130	1000
	47212	■	1.7	4.0	18	12	0.15	0.150	1000
	47218	■	1.7	4.0	24	18	0.15	0.190	1000
4	4738	■	2.2	4.7	14	8	0.15	0.150	1000**
	GR4738	■	2.2	4.7	14	8	0.15	0.150	500 ***
	47312	■	2.2	4.7	18	12	0.15	0.200	1000
6	47318	■	2.2	4.7	24	18	0.15	0.250	1000
	47410	■	2.8	5.4	17	10	0.20	0.210	100**
	47412	■	2.8	5.4	20	12	0.20	0.250	100
10	47418	■	2.8	5.4	26	18	0.20	0.320	100
	47512	■	3.5	6.9	20	12	0.20	0.350	100**
	47518	■	3.5	6.9	26	18	0.20	0.460	100
16	47612	■	4.5	8.4	22	12	0.20	0.450	100**
	47618	■	4.5	8.4	28	18	0.20	0.650	100
16	47712	■	5.8	9.6	24	12	0.20	0.650	100**
	47718	■	5.8	9.6	28	18	0.20	0.800	100