


Insulated solderless terminals, fork type

- ▶ Acc. to DIN 46237 with flared insulation sleeve
- ▶ For fine and superfine stranded conductors
- ▶ High-quality brazing process in the crimp area
- ▶ Fork-type version for simple and direct screw mounting



Characteristics

- Total cross-section: 0.1 - 6 mm²
- Insulated, halogen-free
- Heat resistant to 105° C
- Easy-Entry insulation for easy cable insertion
- Cross-section-dependent colour-coding

Material

- Cu-ETP
- Insulation sleeve: PA

Surface

- Tin-plated

Nominal cross section mm ²	Nominal size to DIN	Part No.	Colour	Dimension mm										Weight/ 100 pcs. ~ kg	Packing unit/pcs
				a1	a2	d1	d2	d3	d4	l	s				
0.1-0.4	--	*619C3	□	--	--	--	3.2	5.0	--	14.0	0.5	0.020	100		
	3.0-1	620C3	■	5	10.5	1.6	3.2	6.0	4.5	16.5	0.8	0.060	100		
	3.5-1	620C35	■	5	10.5	1.6	3.7	6.8	4.5	17.5	0.8	0.060	100		
0.5-1	4.0-1	620C4	■	5	10.5	1.6	4.3	6.8	4.5	17.5	0.8	0.070	100		
	5.0-1	620C5	■	5	10.5	1.6	5.3	10.0	4.5	18.5	0.8	0.090	100		
	--	*620C6	■	5	10.5	1.6	6.5	11.0	4.5	20.5	0.8	0.080	100		
1.5-2.5	3.0-2.5	630C3	■	5	11.5	2.3	3.2	6.0	5.1	17.5	0.8	0.060	100		
	3.5-2.5	630C35	■	5	11.5	2.3	3.7	6.8	5.1	18.5	0.8	0.065	100		
	4.0-2.5	630C4	■	5	11.5	2.3	4.3	6.8	5.1	18.5	0.8	0.080	100		
	5.0-2.5	630C5	■	5	11.5	2.3	5.3	10.0	5.1	20.5	0.8	0.090	100		
	6.0-2.5	630C6	■	5	11.5	2.3	6.5	11.0	5.1	22.5	0.8	0.110	100		
4-6	4.0-6	650C4	□	6	12.5	3.6	4.3	8.0	6.5	20.5	1.0	0.140	100		
	5.0-6	650C5	□	6	12.5	3.6	5.3	10.0	6.5	21.5	1.0	0.160	100		
	6.0-6	650C6	□	6	12.5	3.6	6.5	11.0	6.5	22.5	1.0	0.170	100		
	8.0-6	650C8	□	6	12.5	3.6	8.4	14.0	6.5	25.5	1.0	0.220	100		
	10.0-6	650C10	□	6	12.5	3.6	10.5	18.0	6.5	27.5	1.0	0.280	100		

- ▶ * = not standardized
- ▶ 0.1 - 0.4 mm² not CSA tested
- ▶ **Tools: see chart page 193**