


Insulated pin connectors

▶ For fine and superfine stranded conductors



Characteristics

- Total cross-section: 0.5 - 6 mm²
- Cross-section-dependent colour-coding
- Heat resistant to 70° C

Material

- CuZn (brass)
- Insulation sleeve: PVC

Surface

- Tin-plated to protect against corrosion

Nominal cross section mm ²	Part No.	Colour	Dimension mm				Weight/ 100 pcs. ~ kg	Packing unit/pcs
			Tab dia.	l1	l2	s		
0.5-1	1020	Red	4	22	9	0.38	0.060	100
1.5-2.5	1030	Blue	5	22	9	0.38	0.075	100
4-6	1050	Yellow	5	22	9	0.40	0.110	100

▶ 1.5 - 2.5 mm² and 4 - 6 mm² not CSA tested

▶ **Tools: see chart page 193**

Insulated pin receptacles, fully insulated

▶ For fine and superfine stranded conductors
 ▶ High quality bronze material provides optimum spring characteristic and improved contact strength



Characteristics

- Total cross-section: 0.5 - 6 mm²
- Insulated, halogen-free
- Cross-section-dependent colour-coding
- Heat resistant to 105° C

Material

- CuSnZn (bronze)
- Insulation sleeve: PA

Surface

- Tin-plated

Nominal cross section mm ²	Part No.	Colour	Dimension mm			Weight/ 100 pcs. ~ kg	Packing unit/pcs
			Tab dia.	l1	s		
0.5-1	920V	Red	4	24	0.38	0.065	100
4-6	950V	Yellow	5	27	0.40	0.150	100

▶ 4 - 6 mm² not CSA tested

▶ **Tools: see chart page 193**