

Insulated receptacles, fully insulated

► For fine and superfine stranded conductors



Characteristics

- Total cross-section: 0.5 - 6 mm²
- Insulated, halogen-free
- Cross-section-dependent colour-coding
- Heat resistant: PVC to 70° C, PA to 105° C

Material

- CuZn (brass)
- Insulation sleeve: PVC/PA

Surface

- Tin-plated

Order info

- Now also available in handy plastic boxes for smaller requirements, part number appendix "SB"

Nominal cross section mm ²	Part No.	Colour	Tab thicken.	Tab width	Dimension mm			Insulation material	Weight/ 100 pcs. ~ kg	Packing unit/ pcs
					l1	l2	s			
0.5-1	8201V	■	0.5	2.8	19.0	5.5	0.25	PA	0.07	100
	8201AV	■	0.8	2.8	19.0	5.5	0.25	PA	0.07	100
	8202V	■	0.5	4.8	20.0	7.0	0.30	PVC	0.10	100
	8203V	■	0.8	4.8	20.0	7.0	0.30	PVC	0.10	100
	720V	■	0.8	6.3	21.0	7.5	0.45	PVC	0.08	100*
1.5-2.5	8301V	■	0.5	2.8	20.0	8.0	0.35	PVC	0.14	100
	8301AV	■	0.8	2.8	20.0	8.0	0.35	PVC	0.14	100
	8302V	■	0.5	4.8	20.5	7.0	0.30	PVC	0.11	100
	8303V	■	0.8	4.8	20.5	7.0	0.30	PVC	0.11	100
	730V	■	0.8	6.3	21.0	7.5	0.45	PVC	0.15	100*
4-6	8502V	■	0.5	4.8	20.5	9.5	0.40	PVC	0.15	100
	8503V	■	0.8	4.8	20.5	9.5	0.40	PVC	0.15	100
	750V	■	0.8	6.3	25.5	11.5	0.45	PVC	0.16	100

► * = Also available in small handy packs

► **Tools: see chart page 193**