


Insulated butt connectors

- ▶ For fine and superfine stranded conductors
- ▶ With buttmarks for precise cable insertion



Characteristics

- Total cross-section: 0.1 - 6 mm²
- Insulated, halogen-free
- Cross-section-dependent colour-coding
- Heat resistant to 105° C

Material

- Cu-ETP
- Insulation sleeve: PA

Surface

- Tin-plated

Order info


- Now also available in handy plastic boxes for smaller requirements, part number appendix "SB"

Nominal cross section mm ²	Part No.	Colour	Dimension mm			Weight/ 100 pcs. ~ kg	Packing unit/pcs
			d1	l1	l2		
0.1-0.4	669	Yellow	1.2	20	12	0.030	100
0.5-1	670	Red	1.6	25	15	0.090	100*
1.5-2.5	680	Blue	2.3	25	15	0.115	100*
4-6	700	Yellow	3.6	27	15	0.250	100*

- ▶ * = Also available in small handy packs
- ▶ 0.1 - 0.4 mm² not CSA tested
- ▶ **Tools: see chart page 193**

Insulated butt connectors, with heat shrink insulation

- ▶ For fine and superfine stranded conductors
- ▶ With buttmarks for precise cable insertion
- ▶ With waterproof heat shrink insulation



Characteristics

- Total cross-section: 0.5 - 6 mm²
- Insulated, halogen-free
- Cross-section-dependent colour-coding
- Special crimping tool required
- Heat resistant to 105° C

Material

- Cu-ETP
- Insulation sleeve: PE

Surface

- Tin-plated

Nominal cross section mm ²	Part No.	Colour	Dimension mm			Weight/ 100 pcs. ~ kg	Packing unit/pcs
			d1	l1	l2		
0.5-1	670WS	Red	1.6	36	15	0.12	100
1.5-2.5	680WS	Blue	2.3	36	15	0.15	100
4-6	700WS	Yellow	3.4	41	15	0.25	100

- ▶ **Tools: see chart page 193**